



Specialty Products
and Insulation

Absorption Plus® High Impact Tack Panels

Description

Absorption Plus High Impact Tack acoustical panels are composed of a semi-rigid fiberglass core board with a minimum of 25% recycled glass content and a bonded impact laminate of molded fiberglass. Panel edges are available plain or chemically hardened for greater durability. Acoustical facing materials are bonded to the panel using a low VOC water based adhesive. Standard and optional panel facings are available from a range of industry leading manufacturers. The finished panels enhance interior space acoustics by reducing room reverberation while adding visual impact and interest.

High Impact Features / Benefits

- Superior acoustic performance enhances room acoustics through reduced reverberation.
- High density molded fiberglass laminate provides enhanced durability.
- Custom fabricated panels provide unlimited size, shape, (geometric and curved capability) thickness and edge detail.
- Full range of fabrics, patterns, colors as well as custom imaging for unique visuals.
- The standard 100% polyester faced composite panels are Class A fire rated per ASTM E84 providing a fire safe interior finish material per code requirements.
- Typical lead time of 3 - 4 weeks provides fast order turnaround for quick, on time project completion.
- Panel ship in durable wood crates virtually eliminating shipping damage, claims and resulting project delays.
- A variety of available mounting options to suit any application condition.

Availability

Absorption Plus High Impact Tack panels are used in conjunction with Absorption Plus all, Deck and Cloud, Tack and Baffle panel applications.

High Impact Standard Sizes: 1 1/8", 1 5/8", 2 1/8" thick, up to 4' wide and 10' long

Edge Treatments: Square, Bevel, Chamfer and Radius, plain or chemically hardened

Absorption Plus acoustical panels are available through a network of SPI locations across North America.

Additional product information at www.spi-co.com



Specialty Products
and Insulation

SPI LLC

2101 Rexford Road, Suite 300E


Charlotte, NC 28211

Phone: (855) 519-4044

Web: www.spi-co.com

E-mail: fabteam@spi-co.com

July 2019 - Absorption Plus High Impact Tack



Absorption Plus High Impact Wall, Ceiling/Deck and Cloud Panels (See datasheets for other Absorption Plus products)

Performance Compliance Data

Base Board: Complies to ASTM E84 / UL 723 - Flame Spread 25, Smoke Developed 50, Class A fire rated

SCS Certified - Minimum 25% Recycled Content

Thermal Resistance: R Value 4.3 per inch at 75°F Mean Temp.

Nominal Density: 6 - 7 pcf

Bonded Impact Laminate: 1/8" thick, 16-20 pcf density impact resistant fiberglass

Facings: include 100 % polyester fabric (i.e. Guilford of Maine FR701), and other industry leading manufacturers.

Adhesive: Water based fire retardant, low emitting VOC complying with LEED™ IEQ Credit 4.1

ASTM E84 - Flame Spread 5, Smoke Developed 0

(Properties as reported by manufacturers)

Sound Absorption Coefficients Mounting Type A
per ASTM C423 and ASTM E795, (Composite panel)

Thickness		Frequency, Hz						
Inches	(mm)	125	250	500	1000	2000	4000	NRC
1 1/8"	(29)	0.19	0.58	0.87	0.98	0.94	0.83	0.85
2 1/8"	(54)	0.53	0.88	1.04	0.98	0.86	0.82	0.95

Disclaimer and Limitation of Warranty. The purchaser/user is advised to consult with the appropriate professionals and to read the manufacturer's product information to determine the adequacy or appropriateness of the product for the use intended. SPI makes no claim or representation regarding the use or applicability of the products. Further, SPI makes no warranty, expressed or implied, and disclaims all warranties including warranties of merchantability and fitness for a particular purpose.

*For additional information please visit
Our website www.spi-co.com
Please ask your Sales representative about
our other products and services.*